



Kennel Clad™ Insulated Guillotine Kennel Doors

Customized Framing C-Channel

Unique framing channel provides integrated panel strength and allows for the attachment of the Hidden Top Wall and Floor Seals. Secured with stainless fasteners.

Heavy Duty Channel Side Rails

Constructed with solid extruded 6063-T6 aluminum. Rails are heat treated and feature machined screw slots for easy mounting and fitting adjustments. Each Rail measures 2.5" wide and 48" long. Dual channel design allows for use with any standard 1/4" thick door, as well as the Kennel Clad Insulated Doors.

Hidden Floor Seal

Flexible bulb seal fits tight into customized channel to ensure seal to floor as well as having hidden profile from chewers

Hidden Top Wall Seal


Durable, brush with interior vinyl fin is seated into customized channel. Bridges gap between door and wall ensuring no air leakage when door is closed. Offset and hidden from mischievous dogs

Mounting Slots

Generous adjustment slots measure 1/4" wide x 7/8" long. This allows for proper fitting & adjustment to ensure a smooth door operation

Aluminum Clad Insulated Panel

Air cell polypropylene core is clad with 18-gauge aluminum, framed with customized Channel, affixed with stainless fasteners to provide a heavy duty insulated panel that provides optimum insulation and rugged long life.



KENNEL CLAD™