



MAXSEAL DOOR MOUNTED PREMIUM PET DOORS

POSSIBLE PRODUCTION VARIATIONS

SINGLE OR DUAL FLAP MODEL
10 STANDARD SIZES
10 POWDER COATED COLOR OPTIONS
SECURITY PANEL AVAILABLE IN WHITE OR BLACK
LEFT OR RIGHT SIDE LOADED SECURITY PANELS
CUSTOM SIZE DOORS MADE TO CUSTOMER MEASUREMENTS

Corner Reinforcements

High strength rolled aluminum corner brackets secured with stainless steel set screws. Also has internal aluminum key insert held with industrial strength epoxy.

Heavy Duty Lock Bolt Pin

Features a 1/4 turn lock out, spring-loaded bolt pin that allows for easy one handed operation. Machine finished to match designer security panel handle

Weatherized Vinyl Flexible Flaps

Nylon reinforced, low temperature flexible vinyl PVC. UV protected and treated so that flap will not shrink or yellow. Will remain flexible in cold weather. Flaps are self extinguishing when exposed to flame. Designed to be pet friendly

Heavy Duty Frame

MaxSeal features the strongest frame in the pet door industry. Constructed of 6063-T⁶ high strength extruded aluminum 0.070" - 0.090" thick. Offered in 10 powder coated finishes

Weather Seal Brushes

Heavy duty, dense brush weather seal lines the flap perimeter to eliminate drafts and air leakage

Stainless Steel Strikes / Magnets

Stainless strike plates are riveted to the flap for durability and maintained proper placement to magnet surface. Each Strike plate aligns with an 1 1/2" long Alnico magnet embedded into the frame to create a positive flap seal. (The number of magnets per flap will depend on the size of pet door selected)

Fits Doors 1 1/4" to 2"

The MaxSeal door mounted pet door will self adjust to fit any door from 1 1/4" to 2" in thickness. The MaxSeal is designed for all types of doors, metal, insulated, wood, fiberglass and raised panel surfaced doors.

Folding Panel Handle

Designer folding security panel handle, machined to match the Heavy Duty Lock Bolt Pin. Provides for easy control of panel when inserting or removing from the pet door. Folds down to minimize profile
Note: Panel slides from the top - down in this image. Doors can also be made to have panel slide in from either left or right side

1/2" Insulated Security Locking Panel

Features the strongest, most secure locking security panel of any pet door made. Provides for added insulating protection due to the composite nature of materials. Constructed of corrugated high density Poly Ethylene (HDPE), adhered between 2 sheets of #27 gage aluminum. This core composite is then riveted between 2 sheets of rugged ABS creating a rigid, rugged insulated panel

