



Security Boss® Pet Screen Door Installation

Included Items with Pet Screen Door purchase:

Screen Pet Door
Rubber Spline for connecting screen
Roller Tool
Razor Blade
Low profile Screws
H-Channel attachment

Other tools that you will need

Electric drill
Right Angle
Marker

A SAFETY REMINDER!

Always wear eye protection and gloves when appropriate.

1. Most sliding screen doors are mounted on rollers. Tension screws are usually located near these rollers. They can be loosened to allow easy removal of your screen door. Some brands such as Pella doors have the screen doors attached to rollers suspended from the top of the screen door channel. There are screws along the interior top edge of the screen door and once these are loosened, the door will drop enough to lift out of the channel in the floor.

Remove the host screen door from the sliding channel and lay on flat work surface.



2. Position the pet door on your screen door, spline grooves up. The pet door must be mounted in the bottom corner. *For example, most patio screen doors have the screen spline groove to the exterior; the Pet screen door spline groove should therefore be to the exterior as well.*



3. Mark the horizontal screen cut location on the sliding screen door frame with a pencil. It is best to mark the cut location a 1/8" in from the end of the H channel (Overlay flange) attached to the Pet screen door to allow enough screen material to roll into Pet Screen Door Spline groove. (Point A)



4. Make the same mark at the bottom corner of the overlay flange - bottom corner of your screen pet door; 1/8" in from the end of the H channel. (Point B)



5. Using a marker, draw a straight line on the screen from point A inward and Point B upward. Where they intersect is Point C.



6. Cut screen from Point A to Point C using a straight edge and utility knife.



7. Cut screen from Point C to Point B using a straight edge utility knife.

A Builder square may be helpful for this part of the installation.



8. Cut (Do not pull screen away from spline) along the inside edge of your screen door to remove this section. **DO NOT REMOVE SPLINE.**



9. Position the Security Boss[®] screen pet door over the cut opening. Pet door should be firmly seated into the corner of your sliding screen door.



10. Using the included bit, approximately 1" in from the overlapping flange ends, drill and secure the pet door frame to your screen door and fasten with provided screws. Do not drill completely through your screen door frame.



11. Using the included roller tool and spline, start at Point A and attach the screen to the pet door frame moving towards Point C



12. Repeat same process from Point C to Point B. Keep the screen taut by applying constant pulling pressure to ensure a tight fit.



13. Carefully trim any excess screen

You have installed your Security Boss[®] Screen Pet Door.

